

# Ed-Fi 3.x Student Discipline Incident Association Entity Mapping

## Overview

This document defines the mapping of Aeries data to the Ed-Fi data standard.



**Document Version** 1.0

**Last Updated** 07 Nov 2021

## Status

Ready for v3 certification.

## Description

This association indicates those students who were victims, perpetrators, witnesses, and reporters for a discipline incident.

## Student Discipline Incident Association Links

### Mapping v3.2.0-c

<https://mappingedu.ed-fi.org/#!/entity/07066848-e7ba-ea11-80df-005056b36109/info?dataStandardId=7ec6133d-e7ba-ea11-80df-005056b36109>

### Schema v3.2.0-c

<https://schema.ed-fi.org/datahandbook-v320c/#!/StudentDisciplineIncidentAssociation607>

### API v3.4.0

<https://api.ed-fi.org/v3.4.0/docs/index.html#/studentDisciplineIncidentAssociations>

### Scenarios v3

<https://techdocs.ed-fi.org/display/EDFICERT/v3+Student+Discipline+%3E+StudentDisciplineIncidentAssociation+Scenarios>

## Natural Key

- IncidentIdentifier
- SchoolId
- StudentUniqueId

## Used By

- DisciplineAction.StudentDisciplineIncidentAssociation (as required collection)

## Mapping

Parent	Property	Type	Required	Table	Field	Other	Code / Notes
\	behaviors	List(Of StudentDisciplineIncidentAssociation Behavior)	Required				

behaviors[n]	behaviorDescriptor	BehaviorMapType	Required	ADS	CD (CD2, CD3, CD4, CD5)		GetEdFiCodeValue(BehaviorDescriptor, "ADS", "CD", rowADS!CD)  GetEdFiCodeValue(BehaviorDescriptor, "ADS", "CD", rowADS!CD2)  GetEdFiCodeValue(BehaviorDescriptor, "ADS", "CD", rowADS!CD3)  GetEdFiCodeValue(BehaviorDescriptor, "ADS", "CD", rowADS!CD4)  GetEdFiCodeValue(BehaviorDescriptor, "ADS", "CD", rowADS!CD5)  if the above values are not empty add each one if none exists then add "Other"  This is actually what we would send to EdFi because we store "Behaviors" on a per-student basis, not at the incident level.
behaviors[n]	behaviorDetailedDescription	String	Optional				
\	disciplineIncidentReference	DisciplineIncidentReference	Identity				
disciplineIncidentReference	incidentIdentifier	String	<b>Identity</b>	ADS	IID		GetString(rowADS!IID)
disciplineIncidentReference	schoolId	Integer	<b>Identity</b>	ADS	SCL		GetNullableInteger(rowADS!SCL)
\	studentParticipationCodeDescriptor	Descriptor	<b>Required</b>			'Perpetrator'	GetV3Descriptor("StudentParticipationCodeDescriptor", "Perpetrator")
\	studentReference	StudentReference	Identity				
studentReference	studentUniqueId	String	<b>Identity</b>	ADS	PID		GetString(s("PID"))