

# Ed-Fi 3.x Discipline Incident Entity Mapping

## Overview

This document defines the mapping of Aeries data to the Ed-Fi data standard.



**Document Version** 1.0

**Last Updated** 07 Nov 2021

## Status

Ready for v3 certification.

## Description

This event entity represents an occurrence of an infraction ranging from a minor behavioral problem that disrupts the orderly functioning of a school or classroom (such as tardiness) to a criminal act that results in the involvement of a law enforcement official (such as robbery). A single event (e.g., a fight) is one incident regardless of how many perpetrators or victims are involved. Discipline incidents are events classified as warranting discipline action.

## Discipline Links

### Mapping v3.2.0-c

<https://mappingedu.ed-fi.org/#!/entity/09006848-e7ba-ea11-80df-005056b36109/info?dataStandardId=7ec6133d-e7ba-ea11-80df-005056b36109>

### Schema v3.2.0-c

<https://schema.ed-fi.org/datahandbook-v320c/#!/DisciplineIncident554>

### API v3.4.0

<https://api.ed-fi.org/v3.4.0/docs/index.html#/disciplineIncidents>

### Scenarios v3

<https://techdocs.ed-fi.org/display/EDFICERT/v3+Student+Discipline+%3E+DisciplineIncident+Scenarios>

## Natural Key

- IncidentIdentifier
- SchoolId

## Used By

- StaffDisciplineIncidentAssociation.DisciplineIncident (as required)
- StudentDisciplineIncidentAssociation.DisciplineIncident (as required)

## Mapping

Parent	Property	Type	Required	Table	Field	Other	Code / Note
\	behaviors	List(Of Discipline IncidentBehavior)	Required				
behaviors[n]	behaviors(1)	DisciplineIncident Behavior	Required				
behaviors[n]	behaviorDescriptor	Descriptor	Required				Not Available - Aeries tracks them per student
behaviors[n]	behaviorDetailed Description	String	Optional				
\	caseNumber	String	Optional				
\	incidentCost	Double	Optional				
\	incidentDate	Date	Required	ADS	DT	ADS.DT	GetNullableDate(s("DT"))
\	incidentDescription	String	Optional				
\	incidentIdentifier	String	Identity	ADS	IID	ADS.IID	GetString(s("IID"))

\	IncidentLocationDescriptor	Descriptor	Required	ADS	LCN	ADS.LCN mapped	GetEdFiCodeValue(IncidentLocationDescriptor, "ADS", "LCN", rowADS!LCN)
\	incidentTime	String	Optional	ADS	ET		GetTimeString(s("ET"))
\	reportedToLaw Enforcement	Boolean	Optional	ADS	LNF		GetNullableBoolean(s("LNF"))
\	reporterDescription Descriptor	Descriptor	Required			'Other'	We do not store this in Aeries. Hard Code to 'Other' GetV3Descriptor ("ReporterDescriptionDescriptor", "Other")
\	reporterName	String	Required	ADS	RF	ADS.RF	GetString(s("Referrer"), "Unknown")  set to "Unknown" if blank.
	schoolReference	SchoolReference	Identity				
schoolReference	schoolId	Integer	Identity	ADS	SCL	ADS.SCL	GetNullableInteger(s("SCL"))
\	staffReference	StaffReference	Optional				
staffReference	staffUniqueid	String	Optional				
\	weapons	List(Of DisciplineIncident Weapon)	Optional				
weapons[n]	weapons (1)	DisciplineIncident Weapon	Optional				
weapons[n]	weaponDescriptor	Descriptor	Optional	ADS	WT		GetEdFiCodeValue(WeaponDescriptor, "ADS", "WT", rowWeapon!WT)